

FLOS

09.8302.DY Matte White

Oblique NEW

Designed by Vincent Van Duysen, 2020




LED - Top LED - 8W - 525lm - 4000K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Driver input: 24 V

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Table
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	8
System power (W)	18
Source flux (lm)	827
System flux (lm)	525

Physical

Colour	Matte White
Orientation	Fixed
Net weight (kg)	0.75
IP internal	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Beam Angle:	35°	
h(m)	E(lx)	D(m)
1	252	2.18
2	63	4.36
3	28	6.54
4	16	8.72
5	10	10.90

Luminous flux Luminaire
525 lm

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	46

Electrical

Insulation class	III
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable
Emergency type	No
Induction recharge QI	No
Charging socket/connector	USB-C