

# FLOS

F6486009 White

## String Light - Sphere head - 12mt cable

Designed by Michael Anastassiades, 2014




21W - 1515lm - 2700K

Suspension lamp providing diffused light. Black, white or blue varnished die-cast aluminium body coated with clear soft-touch varnish. Optical diffuser in opal PC. Suspension system of 12 metres with Kevlar reinforced coaxial cable. Available with wall/ceiling connection in black PC and power supply with floor switch in black varnished PC. The on/off switch is electronic with optical and touch dimm mechanism included or touch dimm and CASAMBI Ready version. Dimmer included. Compulsory to add either floor switch or ceiling/wall rose.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8059607041406
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED array
Power (W)	21
System flux (lm)	1515

### Physical

Colour	White
Cord length (mm)	12000
Net weight (kg)	1.12
Package height (mm)	300
Package width (mm)	300
Package length (mm)	300
Package volume (m3)	0.03
IP internal	20

### Download

Mounting instructions	<a href="#">↓ PDF</a>
Mounting instructions	<a href="#">↓ PDF</a>
Mounting instructions	<a href="#">↓ PDF</a>

### Photometric Files


LDT / IES	<a href="#">↓ LDT</a>
-----------	-----------------------

### Technical Drawings

<a href="#">Bim</a>	<a href="#">↓ ZIP</a>
---------------------	-----------------------



## Schematic light drawing



## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only)  
light source by a  
professional

## Photometric

Lighting type	Total
Light distribution	Roto symmetric
CCT (K)	2700

## Electrical

Insulation class	III
Main voltage (Vac)	48
Forward voltage (V)	48
LED voltage Vf (Vdc)	null
Driver	Remote excluded
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Dimmer Integrated
Batteries inside	No
Charging min time	No

## Accessories & Power Supply



REQUIRED

F6484009

Sting Light Floor Switch



REQUIRED

F6484309

Sting Light Floor Switch



REQUIRED

F6482009

String Light Canopy in White



OPTIONAL

F6485009

String Light Cable

## Spare Parts



- |     |   |           |
|-----|---|-----------|
| 01. | Kit with white hooks and white cable clamps             | RF6480109 |
| 02. | Power supply unit for led                               | RF22934   |
| 03. | Kit with allen key and screws for ceiling rose assembly | RF6480200 |
| 03. | Kit with allen key and screws for ceiling rose assembly | RFU648200 |



RF6480109

Kit with white hooks and white cable clamps




RF22934

Power supply unit for led



RF6480200

Kit with allen key and screws for ceiling rose assembly



RFU648200

Kit with allen key and screws for ceiling rose assembly